



# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

## BASIC CHEMICAL SOLUTIONS

### PART I *What is the material and what do I need to know in an emergency?*

#### 1. PRODUCT IDENTIFICATION

**TRADE NAME (AS LABELED):** **BCS ACID BLEND 0112**  
**CHEMICAL NAME/CLASS:** Nitric/Phosphoric Acid Solution  
**PRODUCT USE:** Cleaner  
**SUPPLIER/MANUFACTURER'S NAME:** **BASIC CHEMICAL SOLUTIONS**  
**ADDRESS:** **Corporate Office**  
 525 Seaport Blvd.  
 Redwood City, CA 94063

**BUSINESS PHONE:** 800-411-4227

**EMERGENCY PHONE:** **CHEMTREC: 800-424-9300**

**DATE OF PREPARATION:** May 21, 2004  
**DATE OF REVISION:** March 5, 2009

**Si usted no entiende las Hojas de Informacion de Seguridad sobre Materials, busque a alguien para que se la explique a usted en detalle.**  
**(If you do not understand the Material Safety Data Sheet, find someone to explain it to you in detail.)**

#### 2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	%w/w	EXPOSURE LIMITS IN AIR					
			ACGIH		OSHA			OTHER mg/m <sup>3</sup>
			TLV mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	PEL mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	IDLH	
Nitric Acid 67%	7697-37-2	20-40	5.2	10	5 2, (Vacated 1989 PELs)	4, (Vacated 1989 PELs)	25 ppm	NIOSH REL: 5 STEL: 10 DFG MAKs: 5
Phosphoric Acid 75%	7664-38-2	20-40	1	3	1 1, (Vacated 1989 PELs)	3, (Vacated 1989 PELs)	1000 mg/m <sup>3</sup>	NIOSH REL: 1 STEL: 3
Water and other ingredients. The other ingredients are each present in less than 1 percent concentration in this product.		Balance	The components present in the balance of this product do not contribute any significant, additional hazards. All hazard information pertinent to this product has been presented in the remaining sections of this Material Safety Data Sheet, per the requirements of Federal Occupational Safety and Health Hazard Communication Standard (29 CFR 1910.1200).					

NE = Not Established. C = Ceiling Limit. See Section 16 for Definitions of Terms Used.

NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1993 format.

### 3. HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW:** This product is a clear solution. This solution is corrosive, and can be damaging to contaminated tissue. Ingestion or inhalation of large quantities can be fatal. In the event of fire or spill, adequate precautions must be taken. This solution contains an oxidizer, which can act to initiate and sustain the combustion of flammable materials. If involved in a fire, this product may decompose to produce a variety of compounds (i.e. carbon monoxide, carbon dioxide, phosphorus oxides and nitrogen oxides). Emergency responders must wear the proper personal protective equipment suitable for the situation to which they are responding.

**SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE:** The most significant routes of occupational overexposure are inhalation and contact with skin and eyes. The symptoms of overexposure to this product are as follows:

**INHALATION:** If mists or sprays of this solution are inhaled, this product may cause pulmonary irritation, irritation of the mucus membranes, coughing, and a sore throat. Inhalation of this product may cause damage to the tissues of the respiratory system, producing potentially fatal lung disorders (chemical pneumonitis and pulmonary edema). Prolonged exposure to the fumes may cause erosion of the teeth enamel.

**CONTACT WITH SKIN or EYES:** Contact with the eyes may cause severe irritation, eye burns and permanent eye damage. Contact with the skin may cause severe irritation, skin burns and permanent skin damage. Prolonged exposure may result in ulcerating burns which could leave scars.

**SKIN ABSORPTION:** Skin absorption is not anticipated to be a significant route of over-exposure to any component of this product.




**INGESTION:** Though ingestion is not anticipated to be a significant route of over-exposure to this product, if ingestion does occur burning and irritation of the mouth, throat, esophagus, and other tissues of the digestive system will occur immediately upon contact. Ingestion of large quantities may be fatal.

**INJECTION:** Though injection is not anticipated to be a significant route of over-exposure to this product, if it occurs, may cause local reddening, tissue swelling, and discomfort.

**HEALTH EFFECTS OR RISKS FROM EXPOSURE:** An Explanation in **Lay Terms**.

**ACUTE:** This solution is corrosive, and can burn and damage eyes, skin, mucous membranes, and any other exposed tissue. If inhaled, irritation of the respiratory system may occur, with coughing, and breathing difficulty. Though unlikely to occur during occupational use, ingestion or injection of large quantities may be fatal.

**CHRONIC:** Repeated skin contact with this product may result in dermatitis (inflammation and reddening of the skin).

HAZARDOUS MATERIAL INFORMATION SYSTEM			
HEALT	(BLUE)	3	
FLAMMABILIT	(RED)	0	
REACTIVIT	(YELLOW)	1	
PROTECTIVE			D
EYES	RESPIRATOR	HAND	BODY
	SEE SECTION		
For routine industrial applications			

## PART II *What should I do if a hazardous situation occurs?*

### 4. FIRST-AID MEASURES

**SKIN EXPOSURE:** If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. Victim must seek medical attention.

**EYE EXPOSURE:** If this product enters the eyes, open victim's eyes while under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes. Victim must seek immediate medical attention.

**INHALATION:** If vapors, mists, or sprays of this product are inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Remove or cover gross contamination to avoid exposure to rescuers.

**INGESTION:** If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Victim should rinse mouth with large amounts of water. Victim should drink one glass of milk or water to dilute the ingested material. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow.

Victims of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with victim.

---

## 5. FIRE-FIGHTING MEASURES

FLASH POINT, °C (method): Not flammable.

AUTOIGNITION TEMPERATURE, °C: Not flammable.

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): Not applicable.  
Upper (UEL): Not applicable.

### FIRE EXTINGUISHING MATERIALS:

Water Spray: YES

Carbon Dioxide: NO

Foam: NO

Dry Chemical: NO

Halon: NO

Other: NO.


UNUSUAL FIRE AND EXPLOSION HAZARDS: This product is corrosive, and presents a significant contact hazard to fire-fighters. Nitric Acid, a component of this product is a strong oxidizer which can ignite many organic materials. When involved in a fire, this material may decompose and produce irritating fumes and toxic gases (including carbon monoxide, carbon dioxide, phosphorus oxides and nitrogen oxides).

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment. If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

### NFPA RATING



---

## 6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel.

The proper personal protective equipment for incidental releases (e.g.-1 L of the product released in a well-ventilated area) use impermeable gloves, specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard-hat. Self Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, Select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

Absorb spilled liquid with polypads or other suitable absorbent materials. Neutralize residue with lime or soda ash or other acid neutralizing agent. Decontaminate the area thoroughly. Test area with litmus paper to confirm neutralization. Place all spill residue in a suitable container. Dispose of in accordance with Federal, State and local hazardous waste disposal regulations (see Section 13 – Disposal Considerations.)

---

## PART III *How can I prevent hazardous situations from occurring*

### 7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash hands after handling this product. Do not eat or drink while handling this material. Remove contaminated clothing immediately. Use ventilation and other engineering controls to minimize potential exposure to this product.

STORAGE AND HANDLING PRACTICES: All employees who handle this material should be trained to handle it safely. Avoid breathing mists or sprays generated by this product. Use in a well-ventilated location.

**For Non-Bulk Containers**: Open containers slowly, on a stable surface. Containers of this product must be properly labeled. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers, or in a diked area, as appropriate. Store containers away from incompatible chemicals. Keep container tightly closed when not in use. Wash thoroughly after using this material. Storage areas should be made of fire-resistant materials. If appropriate, post warning signs in storage and use areas. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged.

Empty containers may contain residual liquid. Therefore, empty containers should be handled with care.

---

## 7. HANDLING and STORAGE--CONTINUED

**Bulk Containers:** All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

**Tank Car Shipments:** Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tank (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be clean and free of incompatible chemicals, prior to connection to the tank car or vessel. Valves and hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Decontaminate equipment before maintenance begins by a triple-rinse with water followed, if necessary, by using acid neutralizing agent and an additional rinse. Collect all rinsates and dispose of according to applicable Federal, State, or local procedures.

---

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** If required use a corrosion-resistant ventilation system separate from other exhaust ventilation systems to ensure that there is no potential for overexposure to sprays, or mists of this product and that exposures are below those in section 2. Ensure eyewash/safety shower stations are available near areas where this product is used.

**RESPIRATORY PROTECTION:** Maintain airborne contaminant concentrations below exposure limits listed in Section 2 (Composition and Information on Ingredients). If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, or applicable State regulations. If adequate ventilation is not available or if there is potential for airborne exposure above the exposure limits (listed in Section 2) a respirator may be worn up to respirator exposure limitations, check with respirator equipment manufactures recommendations/limitations. For a higher level of protection use positive pressure supplied air respiration protection or Self Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown. Nitric acid component has poor warning properties.

**EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS:**

Positive pressure, full-facepiece Self Contained Breathing Apparatus; or positive pressure, full-facepiece Self Contained Breathing Apparatus with an auxiliary positive pressure Self Contained Breathing Apparatus.

**EYE PROTECTION:** Splash goggles or safety glasses. Face-shields are required when the operation can generate splashes, sprays or mists.

**HAND PROTECTION:** Wear appropriate gloves for routine industrial use. Use appropriate gloves for spill response, as stated in Section 6 of this MSDS (Accidental Release Measures).

**BODY PROTECTION:** Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from natural rubber or other appropriate materials are generally acceptable, depending upon the task.

---

## 9. PHYSICAL and CHEMICAL PROPERTIES

Physical and chemical properties for Nitric Acid, a main component of this product, are as follows:

RELATIVE VAPOR DENSITY (air = 1): 1

SPECIFIC GRAVITY (water = 1): 1.295 - 1.300

SOLUBILITY IN WATER: Completely soluble.

VAPOR PRESSURE, mm Hg @ 25 °C: 8

ODOR THRESHOLD: Not available.

APPEARANCE AND COLOR: This is a clear liquid with acid odor. The solution may turn yellow to brown upon exposure to light.

HOW TO DETECT THIS SUBSTANCE (warning properties): Litmus paper will turn red upon contact with even low concentrations of this solution.

---

EVAPORATION RATE (n-BuAc=1): >1

MELTING/FREEZING POINT: -19 °C, (-2 °F)

BOILING POINT: 116 °C, (241 °F)

pH: Approximately 1-2 (1% solution)

---

## 10. STABILITY and REACTIVITY

STABILITY: Stable.

DECOMPOSITION PRODUCTS: Thermal decomposition products of this solution can include carbon monoxide, carbon dioxide, phosphorus oxides and nitrogen oxides.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: This product reacts with bases, reducing agents, alcohols, alkali metals, carbides, cyanides, sulfides and metal powders. . Do not mix this product with sodium hypochlorite, sodium bisulfite, Chlorine Sanitizers or Chlorinated Cleaners – a deadly gas can be formed.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid exposure or contact to extreme temperatures and incompatible chemicals.

---

## PART IV *Is there any other useful information about this material?*

---

### 11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: Additional toxicology information for components greater than 1 percent in concentration is provided below.

**NITRIC ACID:**

TDLo (oral, rat) = 2345 mg/kg; reproductive effects

TDLo (oral, rat) = 21150 mg/kg; teratogenic effects

LDLo (oral, human) = 430 mg/kg

LDLo (unreported, man) = 110 mg/kg

**PHOSPHORIC ACID:**

Skin Irritancy (rabbit) = 595 mg/ 24 hours; severe

Skin Irritancy (rabbit) = 0.5 ml/ 75-85%/ 24 hours; corrosive

Skin Irritancy (rabbit) = 0.5 ml/ 85%/ 4 hours; corrosive

Eye Irritancy (rabbit) = 119 mg; severe

Eye Irritancy (rabbit) = 0.1 ml/ 75-85%; corrosive

Eye Irritancy (rabbit) = 17% solution; mild

Acute Skin Contact (rabbit) = 631-7940 mg/kg/ 24 hours; reduced appetite, increasing weakness, collapse, and death

**PHOSPHORIC ACID (Continued):**

LDLo (unreported, man) = 220 mg/kg

TCLo (inhalation, human) = 100 mg/m<sup>3</sup>

LD<sub>50</sub> (oral, rat) 1530 mg/kg

LD<sub>50</sub> (oral, rat) 3500 mg/kg/ 85% aqueous solution

LD<sub>50</sub> (oral, rat) 4200 mg/kg/ 80% aqueous solution

LD<sub>50</sub> (oral, rat) 4400 mg/kg/ 5% aqueous solution

LD<sub>50</sub> (skin, rabbit) 2740 mg/kg

LC<sub>50</sub> (mouse) 25.5 mg/m<sup>3</sup>

LD<sub>50</sub> (oral, mouse) 1250 mg/kg

SUSPECTED CANCER AGENT: The components of this product are not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, CAL/OSHA; and are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

IRRITANCY OF PRODUCT: This product is severely irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of this product and its components on the human reproductive system.

Mutagenicity: This product is not reported to produce mutagenic effects in humans.

Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.

Teratogenicity: This product is not reported to cause teratogenic effects in humans.

Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Studies on test animals exposed to relatively high doses of Nitric Acid (a component of this product) indicate adverse reproductive effects.

---

## 11. TOXICOLOGICAL INFORMATION--CONTINUED

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

BIOLOGICAL EXPOSURE INDICES: Currently there are no Biological Exposure Indices (BEIs) associated with the components of this product.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Skin disorders can be aggravated by over-exposure to this product. Inhalation of this products mists may aggravate respiratory conditions.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate over-exposure to this product.

---

## 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: The components of this product are relatively stable in the environment; they may degrade, after time, into other organic and inorganic constituents.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: This product is harmful or fatal to plant and animal life if released into the environment. As with all chemicals, work practices should be aimed at eliminating environmental releases. Refer to Section 11 (Toxicological Information) for further toxicological data.

EFFECT OF CHEMICAL ON AQUATIC LIFE This product can substantially lower the pH of an aquatic environment and can be extremely toxic to fish and aquatic plants. As with all chemicals, work practices should be aimed at eliminating environmental releases. Additional aquatic data for the components of this product is available as follows:

### PHOSPHORIC ACID:

Food Chain Concentration Potential: Very Low  
TLm (immersion, mosquito fish) = 138 ppm/ 24-96 hours/ turbid water  
Chronic Hazard Level: The abundance of phosphates threatens algal blooms in fresh and some salt waters  
Waterfowl toxicity: No data available  
Biological Oxygen Demand (BOD): None

### NITRIC ACID:

LC<sub>50</sub> (shore crab) = 180 mg/L/ 48 hours (aerated water conditions)  
LC<sub>50</sub> (cockle) = 330-1000 mg/L/ 48 hours (aerated water conditions)  
LC<sub>50</sub> (starfish) = 100-300 mg/L/ 48 hours (aerated water conditions)  
Acute Hazard Level: Toxic to fish NO<sub>3</sub> is toxic to animal life even after neutralization.  
Chronic Hazard Level: Nitrate can feed algal blooms causing eutrophication

---

## 13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

EPA WASTE NUMBER: D002 (Characteristic, Corrosivity), applicable to wastes consisting only of this solution.

---

## 14. TRANSPORTATION INFORMATION

THIS MATERIAL IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Corrosive liquid, acidic, inorganic n.o.s (Nitric Acid, Phosphoric Acid)  
HAZARD CLASS NUMBER and DESCRIPTION: 8 (Corrosive Material)  
UN IDENTIFICATION NUMBER: UN 3264  
PACKING GROUP: II  
DOT LABEL(S) REQUIRED: Corrosive

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000): 154

MARINE POLLUTANT: This product does not contain any components which are designated by the Department of Transportation to be Marine Pollutants. (49 CFR 172.101, Appendix B).

---

## 14. TRANSPORTATION INFORMATION--CONTINUED

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: THIS MATERIAL IS CONSIDERED AS DANGEROUS GOODS. Use the above information for the preparation of Canadian Shipments.

Note: The latest DOT information is provided, please verify all DOT information as it subject to change without notice.

## 15. REGULATORY INFORMATION

**SARA REPORTING REQUIREMENTS:** The components of this product subject to the reporting requirements of Section 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act are as follows.

COMPONENT	SARA 302	SARA 304	SARA 313
Nitric Acid	Yes	Yes	Yes
Phosphoric Acid	No	Yes	Yes

**SARA Threshold Planning Quantity:** Nitric Acid = 1000 lbs.

**TSCA INVENTORY STATUS:** The components of this product are listed on the TSCA Inventory.

**CERCLA REPORTABLE QUANTITY (RQ):** Nitric Acid = 1000 lbs, Phosphoric Acid = 5000 lbs.

**OTHER FEDERAL REGULATIONS:** Not applicable.

**STATE REGULATORY INFORMATION:** Components of this product are covered under specific State regulations, as denoted below:

**Alaska - Designated Toxic and Hazardous Substances:** Nitric Acid, Phosphoric Acid.

**California - Permissible Exposure Limits for Chemical Contaminants:** Nitric Acid, Phosphoric Acid.

**Florida - Substance List:** Nitric Acid, Phosphoric Acid.

**Illinois - Toxic Substance List:** Nitric Acid, Phosphoric Acid.

**Kansas - Section 302/313 List:** Nitric Acid, Phosphoric Acid.

**Massachusetts - Substance List:** Nitric Acid, Phosphoric Acid.

**Minnesota - List of Hazardous Substances:** Nitric Acid, Phosphoric Acid.

**Missouri - Employer Information/Toxic Substance List:** Nitric Acid, Phosphoric Acid.

**New Jersey - Right to Know Hazardous Substance List:** Nitric Acid, Phosphoric Acid.

**North Dakota - List of Hazardous Chemicals, Reportable Quantities:** Nitric Acid, Phosphoric Acid.

**Pennsylvania - Hazardous Substance List:** Nitric Acid, Phosphoric Acid.

**Rhode Island - Hazardous Substance List:** Nitric Acid, Phosphoric Acid.

**Texas - Hazardous Substance List:** Nitric Acid, Phosphoric Acid.

**West Virginia Substance List:** Nitric Acid, Phosphoric Acid.

**Wisconsin - Toxic and Hazardous Substances:** Nitric Acid, Phosphoric Acid.

**CALIFORNIA PROPOSITION 65:** No component of this product is on the California Proposition 65 lists.

**LABELING (Precautionary Statements):** **DANGER!** CORROSIVE MATERIAL! LIQUID AND MIST CAUSE SEVERE BURNS TO ALL BODY TISSUE. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE LUNG DAMAGE. CONTAINS OXIDIZING MATERIAL-CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. Do not get into eyes, on skin or clothing. Avoid breathing spray or mist. Do not take internally. Use with adequate ventilation and employ respiratory protection when exposed to the mist or spray. When handling, wear chemical splash goggles, face shield, rubber gloves and protective clothing. Do not transfer to unlabeled containers. Wash thoroughly after handling. Keep container closed when not in use. **FIRST AID:** In case of contact, immediately flush skin or eyes for at least 15 minutes. If inhaled, move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Do not induce vomiting. **IN CASE OF FIRE:** Use water. **IN CASE OF SPILL:** Neutralize residue with acid neutralizing agent. Refer to MSDS for additional information.



**TARGET ORGANS:** Skin, eyes and respiratory system.

**WHMIS SYMBOLS:**

D1A- Poisonous and Infectious Materials

Very Toxic Materials

E- Corrosive Material



---

## 16. OTHER INFORMATION

**INFORMATION SOURCE:** BASIC CHEMICAL SOLUTIONS.

**PREPARED BY:** BASIC CHEMICAL SOLUTIONS

THIS INFORMATION IS DRAWN FROM RECOGNIZED SOURCES BELIEVED TO BE RELIABLE. BASIC CHEMICAL SOLUTIONS MAKES NO GUARANTEES NOR ASSUMES ANY LIABILITY IN CONNECTION WITH THIS INFORMATION. THE USER SHOULD BE AWARE OF CHANGING TECHNOLOGY, RESEARCH, REGULATIONS AND ANALYTICAL PROCEDURES THAT MAY REQUIRE CHANGES HEREIN. THE ABOVE DATA IS SUPPLIED UPON THE CONDITION THAT PERSONS WILL EVALUATE THIS INFORMATION AND THEN DETERMINE ITS SUITABILITY FOR THEIR USE.

### DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

**CAS #:** This is the Chemical Abstract Service Number which uniquely identifies each constituent. It is used for computer-related searching.

#### EXPOSURE LIMITS IN AIR:

**ACGIH** - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

**TLV - Threshold Limit Value** - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour **Time Weighted Average (TWA)**, the 15-minute **Short Term Exposure Limit**, and the instantaneous **Ceiling Level**. Skin adsorption effects must also be considered.

**OSHA** - U.S. Occupational Safety and Health Administration.

**PEL - Permissible Exposure Limit** - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order.

**IDLH - Immediately Dangerous to Life and Health** - This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. **The DFG - MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called **Recommended Exposure Levels (RELs)**. When no exposure guidelines are established, an entry of **NE** is made for reference.

#### FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the **National Fire Protection Association (NFPA)**. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

#### TOXICOLOGICAL INFORMATION:

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD<sub>50</sub>** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC<sub>50</sub>** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m<sup>3</sup>** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Data from several sources are used to evaluate the cancer-causing potential of the material. The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause death. **BEI** - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

#### REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Other acronyms used are: **Superfund Amendments and Reauthorization Act (SARA)**; the **Toxic Substance Control Act (TSCA)**; Marine Pollutant status according to the **DOT**; California's Safe Drinking Water Act (**Proposition 65**); the **Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA or Superfund)**; and various state regulations. This section also includes information on the precautionary warnings which appear on the materials package label.